



## Holdback Device Model FA.NAS.sb

- Oil / Grease filled, ready to use.
  - Transmit torque (power) in one direction, opposite free
  - Contains bearing supported and sprags.
- Functions: - Backstopping / Overrunning

Model FA.NAS.Sb	Bore		Transmissible Torque Nm	D	L	L1	F	C	b	N	E	Max. Overrun Rpm
	dH7 mm	Keyway mm										
25	20	6x2.8	220	84	50	12	90	16	15	35	65	500
25	25	8x3.3	220	84	50	12	90	16	15	35	65	500
40	20	6x2.8	1440	118	55	15	110	16	15	35	85	450
40	25	8x3.3	1440	118	55	15	110	16	15	35	85	450
40	30	8x3.3	1440	118	55	15	110	16	15	35	85	450
40	35	10x3.3	1440	118	55	15	110	16	15	35	85	450
40	40	12x3.3	1440	118	55	15	110	16	15	35	85	450
70	45	14x3.8	3140	166	80	20	140	25	18	35	120	350
70	50	14x3.8	3140	166	80	20	140	25	18	35	120	350
70	55	16x4.3	3140	166	80	20	140	25	18	35	120	350
70	60	18x4.4	3140	166	80	20	140	25	18	35	120	350
70	65	18x4.4	3140	166	80	20	140	25	18	35	120	350
70	70	20x4.9	3140	166	80	20	140	25	18	35	120	350
90	75	20x4.9	4700	190	100	20	165	30	20	40	130	250
90	80	22x5.4	4700	190	100	20	165	30	20	40	130	250
90	85	22x5.4	4700	190	100	20	165	30	20	40	130	250
90	90	25x5.4	4700	190	100	20	165	30	20	40	130	250

All Dimensions are in m.m. Dimensions / Design subject to modifications. Other sizes on Request.